

# Application of finite-difference time domain and dynamic differential evolution for inverse scattering of a two-dimensional perfectly conducting cylinder in slab medium

**Chi-Hsien Sun**

**Chien-Ching Chiu**

Tamkang University  
Electrical Engineering Department  
No. 151 Yingjhuang Road  
Danshuei Township  
Taipei County 251  
Tamsui, Taiwan  
E-mail: chiu@ee.tku.edu.tw

**Wei Chien**

De Lin Institute of Technology  
Electronic Engineering Department  
No. 1 Lane 380 Qingyun Road  
Tucheng City  
Taipei County 236  
Taiwan, R.O.C.

**Ching-Lieh Li**

Tamkang University  
Electrical Engineering Department  
No. 151 Yingjhuang Road  
Danshuei Township  
Taipei County 251  
Tamsui, Taiwan

---

**Abstract.** We apply the dynamic differential evolution (DDE) algorithm to solve the inverse scattering problem for which a two-dimensional perfectly conducting cylinder with unknown cross section is buried in a dielectric slab medium. The finite-difference time domain method is used to solve the scattering electromagnetic wave of a perfectly conducting cylinder. The inverse problem is resolved by an optimization approach, and the global searching scheme DDE is then employed to search the parameter space. By properly processing the scattered field, some electromagnetic properties can be reconstructed. One is the location of the conducting cylinder, the others is the shape of the perfectly conducting cylinder. This method is tested by several numerical examples, and it is found that the performance of the DDE is robust for reconstructing the perfectly conducting cylinder. Numerical simulations show that even when the measured scattered fields are contaminated with Gaussian noise, the quality of the reconstructed results obtained by the DDE algorithm is very good. © 2010 SPIE and IS&T. [DOI: 10.1117/1.3514737]

---

Paper 10003RR received Jan. 6, 2010; revised manuscript received Sep. 16, 2010; accepted for publication Sep. 21, 2010; published online Dec. 6, 2010

1017-9909/2010/19(4)/043016/9/\$25.00 © 2010 SPIE and IS&T.

## 1 Introduction

The detection and reconstruction of buried and inaccessible scatterers by inverting microwave electromagnetic measurements is a research field of considerable interest because of numerous applications in geophysical prospecting, civil engineering, and nondestructive testing. Numerical inverse scattering studies found in the literature are based on either frequency or time domain approaches. For frequency domain algorithms, the interaction of the entire medium with the incident field must be considered. In contrast, time-domain approaches can exploit causality to limit the region of inversion, potentially reducing the number of unknowns. Time domain inverse scattering problems thus appear quite often in the area of remote sensing. Most of the previously proposed inversion techniques for the inverse problems are formulated in the frequency domain.<sup>1–8</sup> However, the time domain scheme is a potential alternative for the inverse problems because the time domain data contain more information about scatterer than those in the scattered data of single frequency.

However, it is well known that one major difficulty of inverse scattering is its ill-posedness in nature.<sup>9</sup> Ill-posedness